


DAIHAN-brand® -25℃~+150℃ Digital Precise Refrigerated/Heating Bath Circulator, "MaXircu™ CR", ±0.2℃ **NEW**
 with 1×Flat Lid/Digital Fuzzy Control/CFC-free Refrigeration/Certi. & Traceability, Flow 25Lit/min, Lift 4m, 8-/12-/22-/30- Lit.
 정밀 냉동/가열 배스 겸용 써큘레이터, ideal for Evaporators, etc. 친환경 냉매(R-404A) 채용, id. 10 / od. 12mm 외부 순환 노즐



-25℃~ +150℃ Refrigerated / Heating Bath Circulator
 "MaXircu CR-8" & "MaXircu CR-12"



External Circulation Nozzle



Flat Lid, Stainless-steel (Included)



Ex. Multi-use Refrigerated Bath Circulator with Modular Reactor System

- Made in Korea ■ CE Certified ■ PL(Product Liability) Insurance
- with Certificate & Traceability : Controlled by Serial Number, Certificate, Delivery-information, and Traceable Data Base System
- Advanced Refrigerating System Ensures Temperature Performance
- Digital Fuzzy Control System Implementing Superior Temperature Accuracy
- Innovated Powerful Circulation Pump ensures Temp. Uniformity : Internal and External Circulation (Max Flow Rate : 25 Lit./min.)
- Available to Control 1~5Level Circulation speed(Flow Rate)
- Innovated Refrigeration System, CFC-free (R-404A)
- Patented Jog-Dial Control System and Capacitive Touch Button, Digital LCD with Back-Light Function

- * RS232C Interface for Remote Monitoring and Controlling with PC
- * More Faster Cool-down Time * Urethane Foam Insulation
- * All models Built in Caster * Proper Liquid Level Line in Bath
- * Stainless-steel Bath(# 304) for Superior Durability & High Thermal Efficiency.
- * Connection with Evaporator or Viscometer is applicable.
- * User's Self-compensation Function to Control Difference between Real Temperature and Indicated Temperature (± 10.0℃).
- * Warning and Auto-Stop Function in case of Liquid Shortage.
- * Auto-controlled Refrigeration System for Compressor Protection and Power Saving.
- * Locking Mode Supported for Experimental Safety (Input to Jog-Dial can be Disabled)
- * Recommended to Use with Ethyl Alcohol(94~95%) at Under 0℃
- * with High Quality Urethane Foam Insulation

Specifications & Ordering information

Spec.	Models	MaXircu CR-8	MaXircu CR-12	MaXircu CR-22	MaXircu CR-30
Temp. Range & Accuracy		-25℃~ +150℃, ±0.1℃			
Temp. Resolution		0.1℃ - Display, 0.1℃ - Control			
Temp. Uniformity & Probe		±0.2℃ at -10℃, PT100			
Pump		Max Flow Rate : 25Lit/min(Available to Control 1~5Level Flow Rate) Max Pressure : 7.5 psi, Max Lift : 4m			
Bath Volume		8 Lit.	12 Lit.	22 Lit.	30 Lit.
Heating Power		1 kW	1.5 kW	2 kW	2.2 kW
Refrigerator		1/3 HP	1/3 HP	1/2 HP	3/4 HP
Cooling Capacity	at +20℃	300 W	380 W	680 W	850 W
	at 0℃	200 W	250 W	500 W	620 W
	at -20℃	110 W	130 W	300 W	400 W
Refrigerant		CFC -Free(R-404A) Refrigeration System			
Total Power Consumption		1.6 kW	2 kW	2.7 kW	3 kW
Compressor Control		Intelligent Control of Refrigerator for preventing Compressor Overload			
Pump		Max Flow Rate : 25Lit/min, Max Pressure : 7.5 psi, Max Lift : 4m			
External Circulation Nozzle		id.10 / od.12 mm (id. 10 / od.18 mm Silicon tube Connected for inner Circulation)			
Timer & Alarm		99hr 59min (Delay & Continuous run), Error status & Timer-end			
Display		Digital LCD with Back-Light Function			
Controller		Digital Fuzzy Controller with Jog-Dial Knob (Turn+Push)			
Safety Circuit		Over-Temp./-Current protection, Sensor Error Detection, Leakage Breaker			
Material		Stainless-steel (# 304)-Internal, Powder Coated steel-External, 40 mm Thickness Urethane Foaming - Insulation			
Lid & Drain Valve		included Stainless-steel Flat Lid(with Insulation), Ball Valve, Optional Dome Lid,			
Dimension (w×d×h)	Effective Space (mm)	175×153×150	230×181×150	290×220×200	330×290×200
	Internal (mm)	175×320×150	230×350×150	290×390×200	330×460×200
	External (mm)	330×474×752	400×523×807	483×563×850	494×633×906
Packing Size (mm) & Gross Weight (kg)		560×420×922	630×530×972	670×615×1022	740×625×1072
		45 kg	54 kg	63 kg	70 kg
Electrical Reqt.s.		1 Phase, AC 120V, 60Hz or AC 230V, 50 / 60Hz			
Cat. No.	230V	DH.WCR00408	DH.WCR00412	DH.WCR00422	DH.WCR00430
	120V	DH.WCR00508	DH.WCR00512	DH.WCR00522	DH.WCR00530
Price, Each. ₩		1,832,000	1,921,000	2,187,000	2,378,000

* Other Specifications are available upon Customer's Request.

※ 운임 약 ₩ 16,000 별도!

Refrigerated Circulator with Validation (IQ, OQ) Service

DH.WCR30308	Validation Service(IQ, OQ), with "MaXircu CR-8", "CRBV208"	4,000,000
DH.WCR30312	, with "MaXircu CR-12", "CRBV212"	4,000,000
DH.WCR30322	, with "MaXircu CR-22", "CRBV222"	4,000,000
DH.WCR30330	, with "MaXircu CR-30", "CRBV230"	4,000,000

Ea. Price, ₩	4,000,000
	4,000,000
	4,000,000
	4,000,000