



TABLET SPECIFICATION

Model	Tablet 10.1"
Operating System	Windows 10 32-bit
Language	Multilanguages already installed
CPU	Intel® Atom™ Z3735F, Quad core
CPU speed	1,83 GHz
Graphics Card	Intel® HD Graphics 3D Accelerator
Memory	Ram 2,048 GB DDR3L
LCD display	LED 10.1" IPS Multi Touch Screen
LCD resolution	1280x800, 16/10 (WXGA)
Storage	Hdd 32GB
Network	Wireless Bluetooth 4.0
Input/output ports	Micro USB-B, USB Microphone Micro SD card reader Mini HDMI Head-phone
Control Buttons	Auto rotate off, volume control
Battery Technology	Lithium-ion battery, 2x cell
Battery capacity	6000 mAh
Max load	18 W
Connection to the Load	Power supply 7,5V 2A
Dimensions	Thikness 10,5 mm, Height 17,4 cm, Width 25,7 cm
Weight	600 g
Cables included	OTG cable (Micro USB-B to USB-A)
Also included	Instruction manual, Keyboard with touchpad, touch pen.

MICROSCOPE SPECIFICATIONS

Model	Binocular with double layer stage, E-PLAN objectives 4x 10x 40x 100x
Head	Binocular Digital observation head, inclined 30° and rotatable 360°. Diopter adjustment on left eyepieces. Interpupillary adjustment 48-75 mm.
Observation Modes	Brightfield
Eyepieces	Widefield eyepieces WF10X/20 with field number 20.
Nosepiece	Quadruple revolving nosepiece, rotation on ball bearings.
Objectives	E-Plan objectives with mechanical tube length 160mm: -) E-Plan 4X, N.A. 0.10, W.D. 15.2 mm -) E-Plan 10X, N.A. 0.25, W.D. 5.5 mm -) E-Plan 40X, N.A. 0.65, W.D. 0.45 mm -) E-Plan 100X, N.A. 1.25, W.D. 0.13 mm (oil immersion) All objectives are treated with an anti-fungus treatment.
Stage	Double layer with mechanical sliding stage, size 150x139mm, X-Y movement range 75x33mm, specimen holder for one slide. Belt drive in X direction. Vernier scale on X-Y axes, accuracy 0,1mm.

Focusing System	Coaxial coarse and fine focusing mechanism (graduated, 0.002mm) with upper stop, to prevent the contact between objective and specimen. Adjustable tension of coarse focusing knob.
illumination	Light source X-LED ³ type with white LED; light intensity control using a knob on left side of the frame. LED power 3.6W, comparable to a 50W halogen bulb. Color temperature: 6300K. LED average lifetime approx.: 50.000h. Voltage: external power supply 100/240Vac, 50/60Hz, output: 6Vdc 1A. Max. required power: 7W.
Condenser	NA1.25 Abbe condenser, sliding-in, centrable, up-down adjustment by rack&pinion
Dimensions	HEIGHT: 400 mm WIDHT: 235 mm DEPTH: 290 mm WEIGHT: 7,0 kg

CAMERA SPECIFICATIONS

Digital camera resolution	3.14 MegaPixels
Analog camera resolution	NO
Signal output	USB 2.0
Audio Signal	NO
Sensor Size	1/2.5"
Sensor technology	CMOS
Image format	4\3
Full Image size	2048 x 1536
Pixel size	2,2 x 2,2 micron
Frame rate full resolution	5 frames\sec
Frame rate other resolutions	8 FPS (1280x1024), 30FPS (640x480)
Sensitivity	0,53 V/Lux-second (550 nm)
Signal / noise ratio	40 dB
Dynamic range	66.5 dB
Max Exposure time	1,5 sec
ADC conversion	12 BIT
Color Depth	8 BIT
On camera IR Filter	680 nm
Automatic White Balance	Auto - Man
Automatic Gain Control	Auto - Man
Automatic Back light control	Auto - Man
Exposure control	Auto - Man

ACCESSORIES

Calibration Slide	YES
--------------------------	-----

SOFTWARE SPECIFICATIONS

Supplied Software	Optika Vision Lite (full view function is also included for a wider Live Camera view)
Driver type	No driver (microsoft driver)
Capture features	Continuous auto exposure, image size, image capture, compressed video capture
Control parameters	Brightness, gain, exposur time, colors, color enhancement.

GENERAL SPECIFICATIONS

Working temperature	+0 up to +60°C
Storage temperature	-20 up to +70°C
Relative Humidity	45% up to 85%