



Model:

**B-500Ti-3**

Typology:

**LABORATORY MICROSCOPE**

Description:

*Laboratory microscope for routine and research applications.*

*Dye-cast frame, with high stability and ergonomy, for transmitted light observation.*

<b>Illumination</b>	<p><b>Light source type X-LED with white LED;</b> light intensity control using a knob on left side of the frame.          LED power 3W, comparable to an halogen bulb 30-35W.          Color temperature: 6300K          LED average life time approx. 50.000h.          The light exit can be used as a filter holder for additional filters (blue, yellow, frosted).          Voltage: 110/230Vac, 50/60Hz, 0,4/0,8A; Fuse: T3.15A 250V          Max power required: 7W</p>
<b>Observation Modes</b>	Brightfield
<b>Focusing</b>	<p>Coaxial coarse and fine focusing mechanism (graduated, 0.002mm) with upper stop, to prevent the contact between objective and specimen.          Adjustable tension of coarse focusing knob.</p>
<b>Stage</b>	<p>Double layer with mechanical sliding stage, size 175x145mm, X-Y movement range 76x52, specimen holder for two slides.          Vernier scale on the two axes, accuracy 0,1 mm.</p>
<b>Nosepiece</b>	Quintuple revolving nosepiece, rotation on ball bearings.
<b>Head</b>	<p>Trinocular observation head (main head) and binocular (discussion heads), inclined 30° and rotatable 360°.          Diopter adjustment on left eyepiece.          Interpupillary adjustment 55-75 mm.          Multi-viewing device (2 observers simultaneous with the main observer).          Discussion laser pointer (arrow) under the main head.</p>
<b>Eyepieces</b>	Widfield eyepieces WF10X with field number 22 (on main head) and field number 20 (on discussion heads).
<b>Objectives</b>	<p><b>Infinity corrected optical system IOS (Infinity Optical System).</b>          Plan-achromatic objectives infinity corrected, made by following objectives:          -) Plan-achromatic IOS 4X, A.N. 0.10, W.D. 4,7 mm          -) Plan-achromatic IOS 10X, A.N. 0.25, W.D. 4,1 mm          -) Plan-achromatic IOS 40X, A.N. 0.65, W.D. 0,50 mm          -) Plan-achromatic IOS 100X, A.N. 1,25, W.D. 0,08 mm (oil immersion)          All objectives are treated with an anti-fungus treatment.</p>
<b>Condenser</b>	Swing-out type, N.A.0,9 with centering system.
<b>Dimensions</b>	<p><i>Main body:</i>          HEIGHT: 420 mm          WIDTH: 250 mm          DEPTH: 290 mm          WEIGHT: 8 kg  <i>Overall dimensions :</i>          WIDTH: 880 mm          WEIGHT: 12 kg</p>
<b>Accessories</b>	Instruction manual and dust cover included.